



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61M 15/00, B65D 83/14, B05D 7/24	A1	(11) International Publication Number: WO 99/47195 (43) International Publication Date: 23 September 1999 (23.09.99)
(21) International Application Number: PCT/EP99/01757 (22) International Filing Date: 17 March 1999 (17.03.99) (30) Priority Data: 9805938.9 19 March 1998 (19.03.98) GB (71) Applicant (for all designated States except US): GLAXO GROUP LIMITED [GB/GB]; Glaxo Wellcome House, Berkeley Avenue, Greenford, Middlesex UB6 0NN (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): RIEBE, Michael, Thomas [US/US]; Glaxo Wellcome Inc., Five Moore Drive, Research Triangle Park, NC 27709 (US). SCHULZE, Mark, Douglas [US/US]; Glaxo Wellcome Inc., Five Moore Drive, Research Triangle Park, NC 27709 (US). (74) Agent: PIKE, Christopher, G.; Pike & Co., 3 Klondyke, Marlow, Bucks, SL7 2QQ (GB).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: VALVE FOR AEROSOL CONTAINER (57) Abstract <p>The invention provides a valve for an aerosol container suitable for use in dispensing a quantity of the contents thereof. The valve components comprise a fluorinated polymer and/or a fluorinated coating which have been found to reduce drug deposition in the valve.</p> <div data-bbox="719 1167 1357 1906"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

VALVE FOR AEROSOL CONTAINER

The invention provides a valve for an aerosol container suitable for use in dispensing a quantity of the contents thereof and which may be used in the treatment of asthma and other ailments. In particular, the invention provides a valve for a metered dose inhaler suitable for use in dispensing metered doses of medicaments.

Containers for aerosol formulations commonly comprise a vial body (can) coupled to a valve. The valve comprises a valve stem through which the formulations are dispensed. Generally the valve includes a rubber valve seal intended to allow reciprocal movement of the valve stem which prevents leakage of propellant from the container. Metered dose inhalers comprise a valve which is designed to deliver a metered amount of an aerosol formulation to the recipient per actuation. Such a metering valve generally comprises a metering chamber which is of a set volume which aims to administer per actuation an accurate, predetermined dose.

Suitable valves for use in the invention are available from manufacturers well known in the aerosol industry, for example, from Valois, France (eg. DF10, DF30, DF60), Bepak plc, United Kingdom (eg. BK300, BK356, BK357) and 3M-Neotechnic Limited, United Kingdom (eg. SpraymiserTM). The metering valves are used in association with commercially available canisters such as aluminium canisters, suitable for delivering pharmaceutical aerosol formulations.

Aerosol formulations which are generally used comprise a suspension of a medicament, one or

more liquid propellants, optionally with a co-propellant, and optionally an adjuvant such as a solvent or a surfactant, though the invention may be applicable to the dispensing of any aerosol formulation. The aerosol formulation is under pressure in the canister.

It has been found that conventional aerosols, particularly metered dose inhalers, suffer impaired performance due to the deposition of drug particles in the valve component, particularly in the metering chamber. This leads to a high occurrence of inconsistency in the doses of drug being administered which becomes particularly acute over increasing numbers of actuations. The problem of drug deposition in conventional aerosols is particularly exacerbated when excipient-free aerosol formulations are used based on the hydrofluoro alkane (HFA) propellants 134a and 227. It has further been found that drug deposition increases with storage of the aerosol, particularly when the aerosol is stored at high temperature and/or high humidity.

The invention provides a valve for an aerosol in which there is significantly reduced drug deposition compared with conventionally available valves when the valve is used in aerosols comprising an aerosol formulation for inhalation. In particular, the invention provides a metering valve having a metering chamber in which there is significantly reduced drug deposition.

Accordingly the invention relates to a valve for an aerosol container for dispensing a suspension or solution of a substance in a liquid propellant contained therein, wherein the valve comprises a valve body defining a chamber, a transfer passage through which a quantity of substance to be dispensed can pass from the container into the chamber, and dispensing

means which allows the substance to be dispensed, in which the chamber comprises a fluorinated polymer.

The invention further provides an aerosol container which comprises a valve according to the invention, and an inhalation device, preferably a metered dose inhaler, which comprises the aerosol container.

The invention further provides a method of reducing drug deposition in a metering chamber for use in a metered dose inhaler by the use of a fluorinated polymer according to the invention.

The invention further provides a valve for an aerosol container as described hereinabove in which the surface of the chamber, for example, the metering chamber, in contact with the substance to be dispensed is coated with a fluorinated material including fluorine coatings, plastics materials comprising fluorinated materials etc.

The fluorinated coating is preferably a plasma coating, for example, a CF₄ plasma coating. Preferably the fluorinated plasma coating CF₄ is applied to the metering chamber of a metering valve which may be made from any conventionally used plastics material such as Acetal, polyester, etc. The plasma coating may consist of a fluorinated polymer laid down on the surface of the valve component, preferably the chamber, by polymerisation or direct modification of the material surface by interchange of hydrogen ions in the material with fluorine ions. The coating process typically takes place in a vacuum at ambient temperature. The components to be coated are placed inside a chamber which is evacuated. The fluorine

monomer or fluorine source is introduced into the chamber at a controlled rate. The plasma is ignited within the chamber and maintained for a given time at a chosen power setting. At the end of the treatment the plasma is extinguished, the chamber flushed and the products retrieved. In the polymerisation process, a thin layer of plasma polymer will be bonded to the surface of the chamber, preferably a metering chamber, or any other surface of the valve to be coated.

The fluorinated polymer may be selected from any conventionally used fluorinated polymer/copolymer or mixtures thereof or mixture of the fluorinated polymer in combination with non-fluorinated polymers conventionally used in the manufacture of valves, such as acetal, polyester (PBT) as well as polymer blends with, for example, stainless steel (eg. PBT/stainless steel blend (PDX WO96082)), etc. Examples of suitable fluorinated polymers include polytetrafluoroethylene (PTFE), ethylenetetrafluoroethylene (ETFE), polyvinylidene fluoride (PVDF), perfluoroalkoxyalkane (PFA), polyvinyl fluoride (PVF), polychlorotrifluoroethylene (PCTFE), fluorinated ethylenepropylene (FEP) etc. Suitable copolymers include copolymers of tetrafluoroethylene (TFE) with PFA, TFE with hexafluoropropylene (HFP) (available as FEP 6107 and FEP 100 from DYNEON), VDF with HFP (commercially available as Viton A), TFE with perfluoro(propyl vinyl ether) (available as PFA 6515N from DYNEON), a blend of TFE, hexafluoropropylene and vinylidene fluoride (available commercially as THV 200G from DYNEON), etc.

It should be noted, however, that any conventionally available polymer, copolymer or mixture thereof which comprises a fluorinated polymer and which can be used to make the valve for use in an inhaler according to the invention will be suitable. Examples of mixtures of

polymers and/or copolymers comprise, for example, up to 80% by weight fluorinated polymer, optionally up to 40% by weight fluorinated polymer, optionally up to 20% by weight fluorinated polymer or optionally up to 5% by weight of fluorinated polymer. Preferably, fluorinated polymers selected from PTFE, PVF and PCTFE are used as mixtures with non-fluorinated polymers. For example a suitable material is HOSTAFORM X329TM (Hoechst) which is a 5% PTFE/Acetal blend, HOSTAFORM C9021TF which is a 20% PTFE/Acetal blend, PTFE/PBT blends (for example, LNP WL4040), PTFE/PBT/silicone blends (for example, LNP WL4540).

The fluorinated polymers and mixtures thereof used in the invention can be moulded in any conventional manner, for example, by injection moulding, plastic moulding etc.

According to a preferred embodiment of the invention, the valve is a metering valve comprising a metering chamber, a transfer passage through which a quantity of substance to be dispensed can pass from the container into the metering chamber, wherein in the first position the dispensing passage is isolated from the metering chamber and the metering chamber is in communication with the container via the transfer passage, and in the second position the dispensing passage is in communication with the metering chamber and the transfer passage is isolated from the metering chamber.

Medicaments which may be administered in the aerosol formulations, suitably suspended in a liquid propellant, include any drugs useful in inhalation therapy which may be present in a form which is substantially completely insoluble in the selected propellant system. The aerosol formulation, if desired, may comprise one or more active ingredients. Aerosols comprising

two active ingredients in a conventional propellant system are known for the treatment of respiratory disorders such as asthma. Appropriate medicaments may thus be selected from, for example, analgesics, e.g. codeine, dihydromorphine, ergotamine, fentanyl or morphine; anginal preparations, e.g. dilitiazem; antiallergics, e.g. cromolyn, cromoglycate or nedocromil; antibiotics, e.g. cephalosporins, penicillins, streptomycin, sulphonamides or tetracyclines; antihistamines, e.g. methapyrilene; anti-inflammatories, e.g. beclomethasone, flunisolide, fluticasone, tipredane, budesonide, triamcinolone acetonide; antitussives, e.g. noscapine; bronchodilators, e.g. ephedrine, epinephrine, fenoterol, formoterol, isoprenaline, isoproterenol, metaproterenol, phenylephrine, phenylpropanolamine, pirbuterol, repoterol, rimiterol, salbutamol, salmeterol, terbutaline or (-)-4-amino-3,4-dichloro- α -[[[6-[2-(2-pyridinyl)ethoxy]hexyl]amino]methyl]benzenemethanol; diuretics, e.g. amiloride; anticholinergics e.g. ipratropium bromide; hormones, e.g. cortisone, hydrocortisone or prednisolone; and therapeutic proteins and peptides, e.g. glucagon or insulin. It will be clear to a person skilled in the art that, where appropriate, the medicaments will be used in the form of salts (e.g. as alkali metal or amine salts or as acid addition salts) or as esters (e.g. lower alkyl esters) or as solvates (eg hydrates) to optimise the activity and/or stability of the medicament and/or to minimise the solubility of the medicament in the propellant.

Preferably the medicament is selected from bronchodilators and anti-inflammatory steroids of use in the treatment of asthma by inhalation therapy, including salbutamol (e.g. as the sulphate), salmeterol (e.g. as the hydroxynaphthoate known as salmeterol xinafoate), beclomethasone dipropionate or a solvate thereof, fluticasone propionate or (-)-4-amino-3,5-dichloro- α -[[[6-[2-(pyridinyl)ethoxy]hexyl]amino]methyl] benzenemethanol and mixtures thereof.

The particle size of the particulate medicament should be such as to permit inhalation of substantially all of the medicament into the lungs upon administration of the aerosol formulation and will thus desirably be less than 20 microns, preferably in the range 1 to 10 microns, e.g. 1 to 5 microns. The particle size of the medicament or the medicament together with the excipient may be reduced by conventional means, for example by milling, micronisation, spray-drying or controlled recrystallization.

The final aerosol formulation desirably contains 0.0005-10% w/w, preferably 0.0005-5% w/w, especially 0.01-1.0% w/w, of medicament relative to the total weight of the formulation.

Examples of aerosol propellants for the aerosol formulations include CCl_3F (propellant 11) in admixture with CCl_2F_2 (propellant 12) $\text{CF}_2\text{Cl.CF}_2\text{Cl}$ (propellant 14), however, due to the ozone-depleting effects believed to be associated with such propellants, the valve for an aerosol container of the invention is more suitably used with aerosol formulations which comprise so called "ozone-friendly" propellants.

Preferably, the propellants are selected from hydrogen-containing chlorofluorocarbons and fluorocarbons and a number of medicinal aerosol formulations using such propellant systems have been disclosed in, for example, EP 0372777, WO91/04011, WO91/11173, WO91/11495, WO91/14422, WO92/00061, WO92/00062 and WO92/00107.

Suitable propellants include, for example, C_{1-4} hydrogen-containing chlorofluorocarbons such as CH_2ClF , $\text{CClF}_2\text{CHClF}$, CF_3CHClF , $\text{CHF}_2\text{CClF}_2$, CHClFCHF_2 , $\text{CF}_3\text{CH}_2\text{Cl}$ and CClF_2CH_3 ; C_{1-4} hydrogen-containing fluorocarbons such as CHF_2CHF_2 , $\text{CF}_3\text{CH}_2\text{F}$, CHF_2CH_3 and

$\text{CF}_3\text{CHF}\text{CF}_3$ and C_{1-4} perfluorocarbons such as CF_3CF_3 and $\text{CF}_3\text{CF}_2\text{CF}_3$.

Where mixtures of the fluorocarbons or hydrogen-containing chlorofluorocarbons are employed they may be mixtures of the above identified compounds or mixtures, preferably binary mixtures, with other fluorocarbons or hydrogen-containing chlorofluorocarbons for example CHClF_2 , CH_2F_2 and CF_3CH_3 .

A single fluorocarbon or hydrogen-containing chlorofluorocarbon may be employed as the propellant. Particularly preferred as propellants are hydrogen-containing fluorocarbons, especially 1,1,1,2-tetrafluoroethane ($\text{CF}_3\text{CH}_2\text{F}$) (propellant 134a) and 1,1,1,2,3,3,3-heptafluoro-n-propane ($\text{CF}_3\text{CHF}\text{CF}_3$) (propellant 227) or a mixture thereof. The propellants are preferably used in the absence of excipients and adjuvants, such as solvents and surfactants. As used herein "substantially free" refers to formulations which contain no significant amounts of surfactant, for example, less than 0.0001% by weight based upon the weight of the medicament. However, the invention also applies to formulations which include any conventionally used excipients, such as, surfactants etc.

The formulations may be prepared by any conventionally known process, for example, by dispersal of the medicament in the selected propellant in an appropriate container, e.g. with the aid of sonication.

Minimising and preferably avoiding the use of formulation excipients e.g. surfactants, cosolvents etc. in the aerosol formulations is advantageous since the formulations may be substantially taste and odour free, less irritant and less toxic than conventional formulations.

However, such formulations are associated with a higher degree of drug deposition on the valve components. The fluorinated valve according to the invention, particularly the valve having a fluorinated metering chamber, is preferably used to administer formulations substantially free of excipients which has been found to substantially reduce drug deposition in the valve.

The formulations may be filled into canisters suitable for delivering pharmaceutical aerosol formulations. Canisters generally comprise a container capable of withstanding the vapour pressure of the propellant used such as a plastic or plastic-coated glass bottle or preferably a metal can, for example an aluminium can which may optionally be anodised, lacquer- or polymer-coated and/or plastic-coated, which container is closed with a valve according to the invention.

Conventional bulk manufacturing methods and machinery well known to those skilled in the art of pharmaceutical aerosol manufacture may be employed for the preparation of large scale batches for the commercial production of filled canisters. Thus, for example, in one bulk manufacturing method a metering valve is crimped onto an aluminium can to form an empty canister. The medicament is added to a charge vessel and liquified propellant is pressure filled through the charge vessel into a manufacturing vessel. The drug suspension is mixed before recirculation to a filling machine and an aliquot of the drug suspension is then filled through the metering valve into the canister. Typically, in batches prepared for pharmaceutical use, each filled canister is check-weighed, coded with a batch number and packed into a tray for storage before release testing.

Each filled canister may be conveniently fitted into a suitable channelling device prior to use to form a metered dose inhaler for administration of the medicament into the lungs or nasal cavity of a patient. Suitable channelling devices comprise for example a valve actuator and a cylindrical or cone-like passage through which medicament may be delivered from the filled canister via the metering valve to the nose or mouth of a patient e.g. a mouthpiece actuator. A spacer may be placed between the passage and the mouthpiece. Metered dose inhalers are designed to deliver a fixed unit dosage of medicament per actuation or "puff", for example in the range of 10 to 5000 microgram medicament per puff.

According to a further embodiment of the invention, other parts of the inhaler which are also susceptible to drug deposition may comprise the fluorinated polymer of the invention and/or be coated with the fluorinated material according to the invention, for example, the actuator into which the filled canister comprising the valve is fitted for application by the patient. All or part of the actuator, for example, the valve actuator, mouthpiece actuator etc. may comprise the fluorinated polymer/copolymer or mixtures thereof and/or be coated with the fluorinated material.

Administration of medicament may be indicated for the treatment of mild, moderate or severe acute or chronic symptoms or for prophylactic treatment. It will be appreciated that the precise dose administered will depend on the age and condition of the patient, the particular particulate medicament used and the frequency of administration will ultimately be at the discretion of the attendant physician. When combinations of medicaments are employed the dose of each component of the combination will in general be that employed for each component when used alone. Typically, administration may be one or more times, for

example from 1 to 8 times per day, giving for example 1,2,3 or 4 puffs each time.

Each valve actuation, for example, may deliver 25 μg , 50 μg , 100 μg , 200 μg or 250 μg of a medicament. Typically each filled canister for use in a metered dose inhaler contains 60, 100, 120 or 200 metered doses or puffs of medicament.

The invention will now be described further with reference to the accompanying drawing in which Figure 1 is a section through a metering valve according to the invention and to the following Examples which serve to illustrate the invention but are not intended to be limiting.

A valve according to the invention is shown in Figure 1 and comprises a valve body 1 sealed in a ferrule 2 by means of crimping, the ferrule itself being set on the neck of a container (not shown) with interposition of a gasket 3 in a well-known manner.

The valve body 1 is formed at its lower part with a metering chamber 4, and its upper part with a sampling chamber 5 which also acts as a housing for a return spring 6. The metering chamber is made at least in part from a fluorinated polymer and/or a fluorinated coating according to the invention. The words "upper" and "lower" are used for the container when it is in a use orientation with the neck of the container and valve at the lower end of the container which corresponds to the orientation of the valve as shown in Figure 1. Inside the valve body 1 is disposed a valve stem 7, a part 8 of which extends outside the valve through lower stem seal 9 and ferrule 2. The stem part 8 is formed with an inner axial or longitudinal canal 10 opening at the outer end of the stem and in communication with a radial passage 11. The upper portion of stem 7 has a diameter such that it can slide through an opening in an

upper stem seal 12 and will engage the periphery of that opening sufficiently to provide a seal.

Upper stem seal 12 is held in position against a step 13 formed in the valve body 1 between the said lower and upper parts by a sleeve 14 which defines the metering chamber 4 between lower stem seal 9 and upper stem seal 12. The valve stem 7 has a passage 15 which, when the stem is in the inoperative position shown, provides a communication between the metering chamber 4 and sampling chamber 5, which itself communicates with the interior of the container via orifice 26 formed in the side of the valve body 1.

Valve stem 7 is biased downwardly to the inoperative position by return spring 6 and is provided with a shoulder 17 which abuts against lower stem seal 9. In the inoperative position as shown in Figure 1 shoulder 17 abuts against lower stem seal 9 and radial passage 11 opens below lower stem seal 9 so that the metering chamber 4 is isolated from canal 10 and suspension inside cannot escape.

A ring 18 having a "U" shaped cross section extending in a radial direction is disposed around the valve body below orifice 26 so as to form a trough 19 around the valve body. As seen in Figure 1 the ring is formed as a separate component having an inner annular contacting rim of a diameter suitable to provide a friction fit over the upper part of valve body 1, the ring seating against step 13 below the orifice 26. However, the ring 18 may alternatively be formed as an integrally moulded part of valve body 1.

To use the device the container is first shaken to homogenise the suspension within the container. The user then depresses the valve stem 7 against the force of the spring 6. When the valve stem is depressed both ends of the passage 15 come to lie on the side of upper stem

seal 12 remote from the metering chamber 4. Thus a dose is metered within the fluorinated metering chamber. Continued depression of the valve stem will move the radial passage 11 into the metering chamber 4 while the upper stem seal 12 seals against the valve stem body. Thus, the metered dose can exit through the radial passage 11 and the outlet canal 10.

Releasing the valve stem causes it to return to the illustrated position under the force of the spring 6. The passage 15 then once again provides communication between the metering chamber 4 and sampling chamber 6. Accordingly, at this stage liquid passes under pressure from the container through orifice 26, through the passage 15 and thence into the metering chamber 4 to fill it.

In the following Examples each aerosol contains a suspension of a medicament in an excipient-free propellant formulation. In each case aerosols having conventionally available valves made from acetal or polyester are compared with aerosols having valves according to the invention in which either the metering chamber is made from fluorinated ethylene polymer or from polyester which has been plasma coated with CF₄. In each case, the drug deposition generated through use is measured and "Dose Through Use" collection regimes are carried out to analyze doses administered during the life of the inhaler. The formulation tested in each case was an excipient-free propellant formulation comprising fluticasone propionate and 134a propellant.

Valve Drug Deposition Method

The quantity of drug deposited in the valve was measured. The interior valve components include the metering chamber, upper stem gasket and the parts of the upper and lower stem,

which are within the metering chamber. For deposition performed at the beginning of use (BOU) of the inhaler, 2 testfire and 3 manual actuations are taken valve-down followed by 1 manual actuation valve-up to evacuate the metering chamber. Deposition performed on inhalers at end of use (EOU) has used 120 actuation inhalers. Before deposition is performed on these inhalers, 1 manual actuation valve-down is taken followed by 1 manual actuation valve-up to evacuate the metering chamber.

The sample preparation for measuring the valve deposition is the same for both BOU and EOU inhalers. Firstly, the valve stem is washed with acetonitrile. Then, the inhaler is chilled for five minutes in a bath of dry ice and methanol. The valve is removed from the inhaler and the valve interior components are washed quantitatively with acetonitrile into a 50ml volumetric flask containing 25ml water. The drug solution was made to volume and the resultant solution assayed for fluticasone propionate by HPLC.

Dosing Method

The following method was used to evaluate the dosing for the different valve variants for each experiment. The dose was collected as pairs of actuations at the BOU and EOU of the inhaler.

Before the dose collection at BOU, 2 testfire and 4 manual actuations were fired to waste valve-down. Actuations 1 and 2 were fired into a dose trap. The dose trap was washed quantitatively with acetonitrile into a 100ml volumetric flask containing 50ml water. The drug solution was made to volume and the resultant solution assayed for fluticasone propionate by HPLC.

After BOU collections, the inhalers have another 116 actuation fired to waste. The inhalers are at EOU. Actuations 119 and 120 were fired into a dose trap. The dose trap was washed quantitatively with acetonitrile into a 100ml volumetric flask containing 50ml water. The drug solution was made to volume and the resultant solution assayed for fluticasone propionate by HPLC.

Example 1

The EOU interior valve deposition and dosing profile on valves was investigated with different polymer metering chambers. Fluticasone Propionate/Propellant HFA134a Inhalers, 50 microgram, 120 actuation were manufactured using the DF60 valve (acetal components, different polymer metering chambers and nylon ring). The inhalers were stored for a minimum of 2 weeks before analysis of the drug deposited on valve. The deposition and dosing data are presented in Tables 1 and 2.

Table 1: Drug deposition in metering chamber

Composition of Metering Chamber	Amount of drug deposition - mg
Standard acetal	0.26
Standard polyester	0.28
CF4 coated polyester	0.15
FEP 100	0.10
X329 (5% PTFE/acetal blend)	0.18

Table 2: Dosing Data at Actuations 1+2 / 119 + 120 (for a 120 dose product)

Composition of Metering Chamber	Actuation 1 + 2	SD	Actuation 119 + 120	SD	Increase in dose during life of inhaler (µg)
	Dose µg		Dose µg		
Standard acetal	39.6	5%	54.0	12.2%	14.4
Standard polyester	37.7	3.4%	52.3	7.1%	14.6
CF4 coated polyester	41.0	1.6%	49.6	7.5%	8.6
FEP 100	39.0	3.2%	48.1	6.8%	9.1

SD = Standard deviation

Table 2 demonstrates the improvement in the consistency of each dose administered and a reduction in increase of dose through the life of the inhaler using inhalers according to the invention.

Example 2

The EOU interior valve deposition and dosing profile on valves was investigated with PTFE/acetal polymer metering chambers. Fluticasone Propionate/Propellant HFA134a Inhalers, 50 microgram, 120 actuation were manufactured using the DF60 valve and DF60 valve modified with 5%PTFE/acetal in the metering chamber. The inhalers were stored for a minimum of 2 weeks before analysis. The deposition and dosing data are presented in Tables 3 and 4.

Table 3: EOU Interior Valve Drug Deposition

Valve type	Amount of fluticasone propionate deposited (mg)
Standard Valve	0.44
Valve modified with 5%PTFE/acetal	0.32

The valve according to the invention demonstrates significantly lower interior valve deposition than that seen in the standard valve. This is due to the 5%PTFE/acetal polymer metering chamber having fluorine at the surface.

Table 4: Dosing Data

Valve type	Beginning of Use Dose (mcg)		End of Use Dose (mcg)		Increase in dose during life of inhaler (mcg)
	Mean	SD (%)	Mean	SD (%)	
Standard Valve	40.5	4.1	53.0	7.6	12.5
Modified Valve	42.6	2.2	51.4	7.1	8.8

Several experiments were conducted to investigate the quantity of drug deposited on different types of polymer blocks.

The following method was used to analyse the quantity of drug deposited on the polymer blocks for each experiment. Firstly, the fluticasone propionate suspension was evacuated quickly by piercing the MDI can. The valve was then cut from the MDI and the polymer block carefully removed for washing. The polymer block was washed quantitatively with

acetonitrile into a 50ml volumetric flask containing 25ml water. The drug solution was made to volume and the resultant solution assayed for fluticasone propionate by HPLC.

Example 3

The effect of different polymers on the quantity of drug deposited was investigated. The polymer blocks used had the standard injection moulded finish. The polymer blocks were cut to an appropriate size to fit an 8ml-inhaler can. The polymer blocks were then placed into MDI containing a suspension of 0.35% w/w fluticasone propionate in 12g of propellant HFA134a. The inhalers were stored for a minimum of 2 weeks before analysis of the drug deposited on the polymer blocks. The data are presented in Tables 5 and 6.

Table 5: Effect of Polymer Used on Drug Deposition

Polymer Used	Amount of fluticasone propionate deposited (mg)
Acetal	0.23
Hostaform C9021TF (20%PTFE/acetal blend)	0.15
THV200G (TFE, HFP, vinylidene fluoride)	0.14
THV500G (TFE, HFP, vinylidene fluoride)	0.09
PFA6515N (perfluoroalkoxy)	0.05
FEP6107 (fluorinated ethylenepropylene)	0.04
ETFE ET6125 (ethylenetetrafluoroethylene)	0.04

Table 6: Effect of Polymer Used on Drug Deposition

Polymer Used	Amount of fluticasone propionate deposited (mg)
Polyester	0.70
Polyester/PTFE (LNP WL4040)	0.49

The addition of PTFE to polyester reduces the fluticasone deposition significantly compared to pure polyester.

The lowest levels of drug deposition are seen with the polymers with the greater levels of fluorination (PFA, ETFE, and FEP).

Example 4

The effect of fluorine coating the polymer and the quantity of drug deposited was investigated. Acetal was the polymer coated with fluorine. The coating process was the conventionally known plasma coating process.

The polymer blocks were cut to an appropriate size to fit an 8ml-inhaler can. The polymer blocks were then placed into MDI containing a suspension of 0.34% w/w fluticasone propionate in 12g of propellant HFA134a. The inhalers were stored for a minimum of 2 weeks before analysis of the drug deposited on the polymer blocks. The data are present in Table 7.

Table 7: Effect of Fluorine Coating on Drug Deposition

Polymer Used	Amount of fluticasone propionate deposited (mg)
Acetal	0.70
CF4 plasma coating/acetal	0.33

Fluorinating the surface of the acetal by coating has reduced the drug deposition significantly compared to acetal which does not have a fluorinated coating.

It will be understood that the present disclosure is for the purpose of illustration only and the invention extends to modifications, variations and improvements thereto which will be within the ordinary skill of the person skilled in the art.

CLAIMS:

1. Valve for an aerosol container for dispensing a suspension or solution comprising a substance in a liquid propellant contained therein optionally further comprising conventionally used excipients, wherein the valve comprises a valve body defining a chamber, a transfer passage through which a quantity of substance to be dispensed can pass from the container into the chamber, and dispensing means which enables the substance to be dispensed, in which the chamber comprises a fluorinated polymer.
2. Valve according to claim 1 in which the chamber is a metering chamber for use in an aerosol which is a metered dose inhaler.
3. Valve according to claim 1 or claim 2 in which the chamber is made from a plastics material which comprises at least 5% fluorinated polymer.
4. Valve according to claim 1 or claim 2 in which a part or all of the surface of said chamber which is in contact with the substance to be dispensed is coated with a fluorinated material.
5. Valve according to claim 4 in which the coating is a plasma coated CF₄ coating.
6. Valve according to any of claims 1 to 5 in which the substance to be dispensed is a medicament suspended in propellants selected from liquefied HFA 134a, 227 or a mixture thereof.

7. Valve according to claim 6 in which the propellants are substantially free of adjuvants.
8. Valve according to claim 6 or claim 7 in which the medicament is selected from fluticasone propionate, salbutamol, beclomethasone dipropionate, salmeterol, pharmaceutically acceptable salts, solvates or esters thereof and mixtures thereof.
9. Aerosol container comprising a valve according to any of claims 1 to 8.
10. Inhalation device comprising an aerosol container according to claim 9.

1 / 1




FIG. 1.

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/EP 99/01757

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M15/00 B65D83/14 B05D7/24

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M B65D B05D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 96 32099 A (GLAXO WELLCOME INC ;ASHURST IAN C (US); HERMAN CRAIG S (US); LI LI) 17 October 1996	1,2,4,6
Y	see claims 1,13 ---	5
X	GB 1 227 872 A (MINNESOTA MINING & MFG CO) 7 April 1971	1,4
Y	see claims 1,3,5 ---	3
Y	FR 2 740 527 A (VALOIS) 30 April 1997 see claims 1,4 ---	3
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 June 1999

Date of mailing of the international search report

07/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

INTERNATIONAL SEARCH REPORT

Inte.ional Application No

PCT/EP 99/01757

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>DATABASE WPI Section Ch, Week 7742 Derwent Publications Ltd., London, GB; Class A97, AN 77-74880Y XP002107403 & JP 52 106383 A (TOYO AEROSOL IND) , 6 September 1977 see abstract</p>	1
A	<p>US 3 658 214 A (BEARD WALTER C) 25 April 1972 see column 4, line 40 - line 44</p>	3
Y	<p>US 4 693 799 A (YANAGIHARA KENJI ET AL) 15 September 1987 see column 5, line 7 - line 9; claim 1</p>	5

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/01757

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9632099	A	17-10-1996	AU 5480996 A	30-10-1996
			BG 102021 A	31-07-1998
			BR 9604976 A	09-06-1998
			CA 2217950 A	17-10-1996
			CN 1186430 A	01-07-1998
			CZ 9703259 A	18-03-1998
			EP 0820279 A	28-01-1998
			HU 9801526 A	28-10-1998
			NO 974737 A	11-12-1997
			PL 322778 A	16-02-1998
			SK 138897 A	06-05-1998
GB 1227872	A	07-04-1971	AT 306895 B	15-03-1973
			CA 927794 A	05-06-1973
			CH 557418 A	31-12-1974
			CH 547343 A	29-03-1974
			DE 1769355 A	03-12-1970
			DE 1792751 A	16-01-1975
			FR 1565256 A	25-04-1969
			GB 1227873 A	07-04-1971
			NL 6806868 A,B	18-11-1968
			SE 347878 B	21-08-1972
FR 2740527	A	30-04-1997	EP 0858420 A	19-08-1998
			WO 9716360 A	09-05-1997
US 3658214	A	25-04-1972	NONE	
US 4693799	A	15-09-1987	JP 61213221 A	22-09-1986